

HAPMAN



TUBULAR DRAG CONVEYOR



GENTLE HANDLING

Carefully transports fragile materials En masse, preserving product integrity.



SANITARY DESIGN

100% FDA-compliant product-contact materials.



ENCLOSED CONVEYING

Protects product while preventing dust and spillage.




Stainless-Steel Sprocket

Engineered for long-term durability and reliable operation to help minimize unplanned downtime.



Patent-Pending Cable Connector

Simplified, robust design supports easier cable installation and provides a reliable connection during operation.



Food-Grade Cable and Flights

Pre-stretched stainless-steel cable and self-lubricating UHMW flights support clean, gentle, reliable conveying.

ADDITIONAL FEATURES



Tube Connection

Sanitary flange and compression coupling configurations available to meet application requirements.



Pneumatic Auto-Tensioner

Maintains proper cable tension for reliable performance and reduced wear.



Drive Assembly

Full stainless-steel construction with a self-draining bottom cover and clear panels to support cleaning, inspection, and maintenance.

WET AND DRY CLEANING




Sponge Scrubber
Helps apply cleaning agents to the inside of the conveyor during wet or dry cleaning.

Nitrile Wiper
Helps remove particulates from the tube and aids in drying following CIP.


Scouring Pad
Helps loosen and remove stubborn material buildup from inside the conveyor tube.



CIP Capable
Supports in-place wet cleaning with spray nozzles in the drive, idler, brush box, and discharge gates.



Brush Box
Removes debris from the cable and flights during operation.



Air Knife
Removes particulates from the cable and flights during operation.

COMMON CONFIGURATIONS

CablePro can be configured to fit your facility layout and process requirements.



CONVEYOR CAPACITY

CABLE SPEED (ft/min)	4" CONVEYOR		6" CONVEYOR	
	Capacity (ft³/min)	Conveying Rate (lb/hr)	Capacity (ft³/min)	Conveying Rate (lb/hr)
40	2.5	6,000	6	14,400
60	3.75	9,000	9	21,600
80	5	12,000	12	28,800
120	7.5	18,000	17.5	42,000
140	8.75	21,000	20.5	49,200

Based on 40 lb/ft³ bulk density and approximately 80% pocket fill.



PERFORMANTEE®
The Original Performance Guarantee

**YOUR EQUIPMENT WILL
PERFORM AS PROMISED.
GUARANTEED.**

100% OPERATIONAL GUARANTEE. | LIFETIME PROMISE.



Learn more at
hapman.com